

Tubo rígido EN 10305-4 (métrico) TrAle

Tubo rígido EN 10305-4 (métrico)

**Tubo rígido E235 (standard) - 6 mts****Página: 1/1****Especificaciones:** Tubo de acero sin soldadura**Norma:** EN 10305-4

Artículo	Ø ext	Ø in	P. Trabajo (bar)	Peso (kg/m)	L
<b>TH0060100</b>	6	4	365	0,123	- 6 MTS
<b>TH0080100</b>	8	6	259	0,173	- 6 MTS
<b>TH0080150</b>	8	5	423	0,240	- 6 MTS
<b>TH0100150</b>	10	7	321	0,314	- 6 MTS
<b>TH0120150</b>	12	9	259	0,388	- 6 MTS
<b>TH0140200</b>	14	10	303	0,592	- 6 MTS
<b>TH0150150</b>	15	12	201	0,499	- 6 MTS
<b>TH0160200</b>	16	12	259	0,690	- 6 MTS
<b>TH0180200</b>	18	14	226	0,789	- 6 MTS
<b>TH0200300</b>	20	14	321	1,258	- 6 MTS
<b>TH0220200</b>	22	18	181	0,986	- 6 MTS
<b>TH0250300</b>	25	19	247	1,628	- 6 MTS
<b>TH0280200</b>	28	24	139	1,282	- 6 MTS
<b>TH0300300</b>	30	24	201	1,997	- 6 MTS
<b>TH0350300</b>	35	29	169	2,367	- 6 MTS
<b>TH0420300</b>	42	36	139	2,855	- 6 MTS

Los tubos se suministran en largos comerciales de 6 m (±100 mm)

Tubo rígido EN 10305-4 (métrico) TrAle

Tubo rígido EN 10305-4 (métrico)

## Tubo rígido E235 (Cromo III) - 6 mts

Página: 1/1



**Especificaciones:** Tubo de acero sin soldadura. Tratamiento superficial CrIII

**Norma:** EN 10305-4

Artículo	Ø ext	Ø in	P. Trabajo (bar)	Peso (kg/m)	L
THZ060100	6	4	365	0,123	- 6 MTS
THZ080100	8	6	259	0,173	- 6 MTS
THZ080150	8	5	423	0,240	- 6 MTS
THZ100150	10	7	321	0,314	- 6 MTS
THZ120150	12	9	259	0,388	- 6 MTS
THZ140200	14	10	303	0,592	- 6 MTS
THZ150150	15	12	201	0,499	- 6 MTS
THZ150200	15	11	279	0,641	- 6 MTS
THZ160200	16	12	259	0,690	- 6 MTS
THZ180150	18	15	164	0,610	- 6 MTS
THZ180200	18	14	226	0,789	- 6 MTS
THZ200300	20	14	321	1,258	- 6 MTS
THZ220200	22	18	189	0,986	- 6 MTS
THZ250300	25	19	247	1,628	- 6 MTS
THZ280200	28	24	139	1,282	- 6 MTS
THZ300400	30	22	279	2,565	- 6 MTS
THZ350300	35	29	169	2,367	- 6 MTS
THZ420300	42	36	139	2,885	- 6 MTS
THZ380400	38	30	213	3,354	- 6 MTS

Los tubos se suministran en largos comerciales de 6 m ( $\pm 100$  mm)

Tubo rígido EN 10305-4 (métrico) TrAle

Tubo rígido EN 10305-4 (métrico)

## Tubo rígido E235 (standard) - 3 mts

Página: 1/1



**Especificaciones:** Tubo de acero sin soldadura

**Norme:** EN 10305-4

Artículo	Ø ext	Ø in	P. Trabajo (bar)	Peso (kg/m)	L
TH0060100-3	6	4	365	0,123	- 3 MTS
TH0080100-3	8	6	259	0,173	- 3 MTS
TH0080150-3	8	5	423	0,240	- 3 MTS
TH0100150-3	10	7	321	0,314	- 3 MTS
TH0120150-3	12	9	259	0,388	- 3 MTS
TH0140200-3	14	10	303	0,592	- 3 MTS
TH0150150-3	15	12	201	0,499	- 3 MTS
TH0160200-3	16	12	259	0,690	- 3 MTS
TH0180200-3	18	14	226	0,789	- 3 MTS
TH0200300-3	20	14	321	1,258	- 3 MTS
TH0220200-3	22	18	181	0,986	- 3 MTS
TH0250300-3	25	19	247	1,628	- 3 MTS
TH0280200-3	28	24	139	1,282	- 3 MTS
TH0300300-3	30	24	201	1,997	- 3 MTS
TH0350300-3	35	29	169	2,367	- 3 MTS
TH0420300-3	42	36	139	2,855	- 3 MTS

Los tubos se suministran en largos comerciales de 3 m (±100 mm)

Tubo rígido EN 10305-4 (métrico) TrAle

Tubo rígido EN 10305-4 (métrico)

## Tubo rígido E235 (Cromo III) - 3 mts

Página: 1/1



**Especificaciones:** Tubo de acero sin soldadura. Tratamiento superficial CrIII

**Norme:** EN 10305-4

Artículo	Ø ext	Ø in	P. Trabajo (bar)	Peso (kg/m)	L
THZ060100-3	6	4	507	0,123	- 3 MTS
THZ080100-3	8	6	860	0,173	- 3 MTS
THZ080150-3	8	5	588	0,240	- 3 MTS
THZ100150-3	10	7	446	0,314	- 3 MTS
THZ120150-3	12	9	360	0,388	- 3 MTS
THZ140200-3	14	10	421	0,592	- 3 MTS
THZ150150-3	15	12	279	0,499	- 3 MTS
THZ150200-3	15	11	388	0,641	- 3 MTS
THZ160200-3	16	12	360	0,690	- 3 MTS
THZ180150-3	18	15	228	0,610	- 3 MTS
THZ180200-3	18	14	314	0,789	- 3 MTS
THZ200300-3	20	14	446	1,258	- 3 MTS
THZ220200-3	22	18	251	0,986	- 3 MTS
THZ250300-3	25	19	343	1,628	- 3 MTS
THZ280200-3	28	24	193	1,282	- 3 MTS
THZ300400-3	30	22	388	2,565	- 3 MTS
THZ350300-3	35	29	235	2,367	- 3 MTS
THZ380400-3	38	30	295	3,354	- 3 MTS
THZ420300-3	42	36	193	2,885	- 3 MTS

Los tubos se suministran en largos comerciales de 3 m (±100 mm)