

Acoples EXPRESS NF E-29-573

EXPRESS latón

EXPRESS latón- Rosca hembra BSP




Normas: NF E-29573

Artículo	R1	Distancia entre garras (D)
BREX0104	1/4"	40,5 mm
BREX0106	3/8"	40,5 mm
BREX0108	1/2"	40,5 mm
BREX0112	3/4"	40,5 mm
BREX0116	1"	40,5 mm
BREX0120	1" 1/4	40,5 mm

Acoples EXPRESS NF E-29-573

EXPRESS latón

EXPRESS latón- Rosca macho BSP




Normas: NF E-29573

Artículo	R1	Distancia entre garras (D)
BREX0204	1/4"	40,5 mm
BREX0206	3/8"	40,5 mm
BREX0208	1/2"	40,5 mm
BREX0212	3/4"	40,5 mm
BREX0216	1"	40,5 mm
BREX0220	1" 1/4	40,5 mm

Acoples EXPRESS NF E-29-573

EXPRESS latón

EXPRESS latón- Tapón



Normas: NF E-29573

Artículo	Detalles	Distancia entre garras (D)
BREX04	Tapón	40,5 mm

Acoples EXPRESS NF E-29-573

EXPRESS latón

EXPRESS latón- Para manguera



Normas: NF E-29573

Artículo	DN	Distancia entre garras (D)
BREX0508	8	40,5 mm
BREX0510	10	40,5 mm
BREX0513	13	40,5 mm
BREX0514		
BREX0516	16	40,5 mm
BREX0517		
BREX0519	19	40,5 mm
BREX0525	25	40,5 mm
BREX0532	32	40,5 mm